

Fresh Water Salt System (Soft Water—Target is 25-75 PPM of Calcium—Pay Careful attention to Highlighted and Italicized points below). ***If FW IQ monitor is installed, it MUST be DISABLED until later.***

Start Up

Fill with soft water if available (consider the “On-The-Go” water softener as an option)

Remove Metals – use clean screen and stain and scale control

Adjust pH and TA

(You may add your salt at this time. Make sure your output level is 0)

New Step → AFTER 4 HOURS, ADD 1 OUNCE OF PHOSPHATE REMOVER-RUN CLEAN CYCLE

If you did NOT use soft water, place Vanishing Act water softening bag in your hot tub

The standard size reduces a maximum of 150 PPM in our smallest hot tub

After 24 hrs

Clean filters – rinse thoroughly ***repeat on day 2 and 3***

Add Salt according to chart on bottle with jets running if you didn't on day 1

Adjust System Output to 10

Remove Vanishing Act if applicable

If Hardness not 25-75 PPM perform another treatment of Vanishing ACT

Shock with Sodium Hypochlorite (liquid chlorine/bleach) 16 oz

Can use after verifying chlorine levels not above 5PPM (usually about 2 Hrs)

After 24 hours

Check chlorine levels daily

If water is cloudy - Add 1 cup of liquid chlorine Repeat Daily

If chlorine above 5 PPM Lower output level by 1, go back to check daily

If chlorine is 3-5 Proceed to “Every 10 Days” check

If chlorine check below 2 Raise output level by 1 go back to check daily

Once your pH and your chlorine levels are good, ENABLE your FW IQ monitor if applicable

Every 10 days

You will be reminded or do so when you think about it, 10 day reminder must be reset

Check chlorine levels adjust output level if necessary

If 0, adjust output AND turn boost on (will run in boost mode for 24 Hrs)

Adjust pH and/or TA if necessary with pH adjusters

Reset 10 day timer

Every 30 days

New Step → ADD 1/4 Oz OF PHOSPHATE REMOVER-RUN CLEAN CYCLE rinse filters following day

Shock with 1 cup of liquid chlorine or set boost

Check chlorine levels and adjust output if necessary

Every 120 days

Change salt cartridge – you will be reminded

Follow directions on screen when you push Change Cartridge

Clean filters if necessary

Every 365-540 days

Change water

NOTE: If heavy bather load is anticipated or if water appears cloudy, shock with liquid chlorine prior to activity and after activity with 1 cup liquid chlorine. An alternative is to adjust salt system to Boost 24 hours prior and 24 hours after.

Alternate (for owners whose usage is NOT consistent), ie sometimes 1-2 a week other times more:

After achieving proper Chlorine Levels (see start-up procedures above), maintain you tub at a low level of sanitizer (output levels 2-4 depending on size of spa). After EACH use, activate the Boost button within the salt system menu.